20" LCD TV

T20028

www.nl-mirai.com

MIRAI

DCI
Dynamic Color Improvement

5 Picture Mode

SLEEP feature
30/60/90/120/OFF(min.)

DUAL SCART

Auto Contrast

2 year warranty

20" LCD TV

T20028	
Screen Size	408(H) x 306(V)
Aspect Ratio	4 : 3
Pixel Pitch	0.2125(H) x 0.6375(V)mm
Panel Resolution	640 x 480
Brightness	450 cd/m^2
Contrast Ratio (typ.)	400 : 1
Response Time (typ.)	16 ms
Viewing Angles (typ.)	150°(H) / 130°(V)
Display Color	16.7M
Tuner System	PAL, SECAM, NTSC Video
Standard TV	B/G, D/K, I, L/L'
Control Panel	Power(On/Off), Source Select(TV/Video/SCART 1/SCART 2) Menu(OSD) Operation, Channel Up, Channel Down, Volume +, Volume -, IR Receiver
Terminal I/O	Earphone Output(3.5mm jack), Composite AV/S-Video+R/L Input(S-Video is priority), TV Antenna / CATV Input, Full SCART - SCART 1: CVBS/S-RGB(IN), TV(OUT) SCART 2: CVBS/S-RGB(IN), AV/TV(OUT)
Support Timing	480i / 480p / 576i / 576p
Speaker	3W x 2
User Controls	Contrast, Brightness, Sharpness, Colour, Green Enhancement, Sky Enhancement, Red Enhancement, Skin Tone, GAMMA, Country, CH-Scan, Manual Scan, PR-Edit, Fine Tune, Bass, Treble, Balance, Audio Mode(Off-Loudness-Surround-Loudness/Surround), Language, Auto Contrast
Pic-Mode	Standard / Nature / High Bright / Cinema / User
Sleep Timer Function	Off / 30 min. / 60 min. / 90 min. / 120 min.
Teletext	10 pages
Power Supply	AC 100-240 V, 2A, 50/60Hz
Power Consumption	Operation≤80W, Standby<1W
Safety	UL, cUL, CB, TUV-GS, Gost-R
EMC	CE, FCC (Class B)
Accessories	Remote Control, Batteries, User Manual
VESA mounting	100 x 100 mm
System Dimension	476(W) x 500(H) x 160(T) mm
Carton Size	760(W) x 600(H) x 260(T) mm
N.W.	5.3 Kg
G.W.	6.9 Kg

Jupiterstraat 106, 2132 HE Hoofddorp, The Netherlands
TEL +31 (0)23 567 10 58 FAX +31 (0)23 567 10 67 sales@nl-mirai.com